









## Sectional Screens – technical information

### Constructional Data

Articulated screen type External/internal article Fastening	Connecting material	Article width	Article height	Smallest radius in unwound state	Profile		
<b>1 FLEXPRO 1</b> steel/steel Glued and riveted	Plastic strip	15/15	2,0/2,0	40			
<b>2 FLEXPRO 2</b> steel/brass Glued and riveted	Plastic strip	15/15	2,0/2,0	40			
<b>3 FLEXPRO 3</b> steel/ aluminiumGlued and riveted	Plastic strip	15/15	2,0/2,0	40			
<b>4 FLEXPRO 4</b> aluminium semicircular Glued and riveted	Plastic strip	16	3,0	21			
<b>5 FLEXPRO 5</b> aluminium semicircular /aluminiumGlued and riveted	Plastic strip	16/15	3,0/2,0	35			
<b>6 FLEXWALK</b> Hollow aluminium anodised profile Glued and riveted	Plastic or stainless steel strip	22	18	10,0	8,0	40*	
<b>7 FLEXSTAR-C/-S</b> Hollow aluminium anodised profile** Mechanical lock	Connection using plastic, plastic tops	20	5,5	35			
<b>8 FLEXSTAR-CR</b> Hollow aluminium anodised profile** Mechanical lock	Connection using plastic	25	8,0	Upon request			

\* Only with plastic strip, with steel strip 100 mm

\*\* Possible to insert visors of polycarbonate or foil for entrance gate